UltraNeo 340

DESCRIPTION AND GENERAL PROPERTIES

- Material Neoprene and natural latex
- Length (cm) 38
- Thickness (mm) 1.15
- Wrist Scalloped cuff
- Colour/Color Black
- Interior finish Textile support
- Exterior finish Smooth
- Size / EAN 7 8 9 10
- Packaging 1 pair/bag 5 pairs/box 50 pairs/carton
- Complementary information Guaranteed without silicone



PERFORMANCE RESULTS

Certification category 3

0334







EN ISO 374-1

Type A

UVWXYZ

D

F

F

G

Methanol

Acetone

Toluene

Diethylamine

Ethyl acetate

Acetonitrile

Dichloromethane

Carbon Disulfide

Tetrahydrofurane

ANSI



Dexterity EN 420:5/5



PERFORMANCE LEVELS 0-4 0-5 0-4 0-4 A-F (P) Impact protection Cut resistance according to ISO 13997 □ Puncture resistance Tear resistance ☐ Blade cut resistance

THERMAL RISKS EN 407 heat and fire

L Abrasion resistance

L Burning behaviour

PERFORMANCE LEVELS 0-4 0-4 0-4 0-4 0-4 Resistance to large quantities of molten metal Resistance to small drops of molten metal Radiant heat resistant Convective heat resistance Contact heat resistance

CHEMICAL RISKS

EN ISO 374-1 Type B

EN ISO 374-1 Type C

- n-Heptane
- Sodium hydroxide 40%
- Sulphuric acid 96% M Nitric acid 65%
- N Acetic acid 99%
- 0 Ammonia 25%
- Hydrogen peroxide 30%
- Hydrofluoric acid 40%
- Formaldehyde 37%

CUT RESISTANCE

A7 ≥ 4000 G **A1** ≥ 200 G **A4** ≥ 1500 G **A2** ≥ 500 G **A5** ≥ 2200 G **A8** ≥ 5000 G **A3** ≥ 1000 G **A6** > 3000 G **A9** > 6000 G

MICRO-ORGANISMS

EN ISO 374-5



Potection against bacteria,

EN ISO 374-5



Potection against bacteria, fungi, virus

VIRUS



COLD HAZARDS

PERFORMANCE LEVELS 0-4 0-4 0 or 1 Water permeability
■ Water permea Contact cold resistance Convective cold resistance

RADIOACTIVE CONTAMINATION

For more details: www.mapa-pro.com



SPECIFIC ADVANTAGES

- Suitable for long-term wear; added comfort of textile support
- Great dexterity, due to the gloves reduced thickness
- Previous name: Neotex 340

MAIN FIELDS OF USE

Automotive/mechanical industry

· Battery, pump, and compressor manufacturing

Other industries

- Timber treatment
- Industrial cleaning, maintenance

Chemical industry

• Handling and transporting chemicals

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at the workplace may differ from the "CE"-type tests.
- It is not recommended for persons sensitized to natural latex, , thiazoles and dithiocarbamates to use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service MAPA PROFESSIONNEL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

Storage conditions

• Store the gloves in their original packaging at a temperature not below 5°C.

Laundering conditions

- Before taking off the gloves, clean them as appropriate :
- in use with paints, pigments and inks : wipe with a clean cloth dampened with a suitable
- solvent, and rub over with a dry cloth
- in use with a solvent (diluents, etc...): rub over with a dry cloth
- in use with acids or alkalines : thoroughly rinse the gloves under runningwater, and rub over with a dry cloth
- Caution : using the gloves or submitting them to another cleaning or laundering process can alter their performance levels.

Drying conditions

• Ensure the inside of the gloves is dry before putting them on again.

LEGISLATION

This product is not classified hazardous according to the regulation (EC) $n^21272/2008$ of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation $n^21907/2006$ of the European Parliament and of the Council (REACH).

- UE type certificate or CE type examination certificate: 0075/014/162/12/18/2964
- Issued by the notified body nr: nr. 0075 C.T.C 4, rue Hermann Frenkel 69367 Lyon cedex 07 France
- Quality assurance certificat: nr. 0334 Asqual 14 rue des Reculettes -F-75013 PARIS

