

Email: marketing@douyee.com.sg Website: www.douyee.com

## **Product Data Sheet**

PRODUCT CODE / PART NUMBER: DY6008-HS618C-1G-PU/PU-S2SRFO-SK-SIZE



PRODUCT: Static Dissipative Safety Shoes, Black

BRAND NAME: **EUROSTAT**<sup>®</sup> Safetykey

## **FEATURES:**

This safety shoe is made of 3D-mesh Polyester + TPU Heat Seal Upper, 3D-mesh Lining, EUROSTAT® PU Insock, Composite Toe Cap and Double Density PU/PU Outsole.

- 200J Impact Resistant
- 15KN Compression Resistant
- Light Weight, Slip-On with Shoelaces
- Water Resistant and Comfortable Upper
- Non-Marking and Slip Resistant (SR) Outsole Resistant to Fuel Oil (FO) and Most Chemicals



CE

## **Specifications**

Item	Properties / Typical Values	Test Method					
Materials	Upper : 3D-mesh Polyester + TPU Heat Seal Toe Cap : Composite Midsole : Static Dissipative PU						
Et	Outsole : Static Dissipative PU	ANICI/ECD CTM0 1					
Footwear only Resistance	$< 1.0 \times 10^9 \text{ ohms}$	ANSI/ESD STM9.1					
Footwear System Resistance	$< 1.0 \times 10^9 \text{ ohms}$	ANSI/ESD STM9.1					
Electrical System Resistance of a person wearing footwear while standing on conductive flooring	$< 1.0 \times 10^9 \text{ ohms}$	ANSI/ESD STM97.1					
Color	Upper : Black						
	Midsole : Black						
	Outsole : Blue						
Sizes (European)	36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46 & 47						
Conformity	1) The safety footwear detailed herein meets the criteria of in accordance with Article Annex V, including the appearance in Essential Health and Safety Requirements of the PPE for Category II products. This has been shown through ISO 20345: 2022 and examination of the Technic (Category: S2SRFO)	ing the application clauses of the the PPE Regulation EU 2016/425 a through satisfactory testing to EN					

PU OUTSOLE	COMPOSITE TOE CAP				

Size	36	37	38	39	40	41	42	43	44	45	46	47
Average weight per pair (g)	945	979	1012	1046	1079	1113	1147	1179	1214	1247	1280	1314

Date: 2025 / 2026