

Solo 997

DESCRIPTION AND GENERAL PROPERTIES

- Material Nitrile
- Length (cm) 24
- Thickness (mm) 0.1
- Colour/Color Blue
- Interior finish Chlorinated
- Exterior finish Smooth with pebbled fingertips
- Size / EAN 6 7 8 9
- Packaging 100 gloves/box - 1000 gloves/carton



PERFORMANCE RESULTS

Certification category 3

CE 0334



JKT

Legends

EN 388 MECHANICAL HAZARDS



PERFORMANCE LEVELS

0-4 0-5 0-4 0-4 0-4 A-F (P)

Impact protection
Cut resistance according to ISO 13997
Puncture resistance
Tear resistance
Blade cut resistance
Abrasion resistance

EN 407 THERMAL RISKS
heat and fire

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4

Resistance to large quantities of molten metal
Resistance to small drops of molten metal
Radiant heat resistant
Convective heat resistance
Contact heat resistance
Burning behaviour

CHEMICAL RISKS

EN ISO 374-1



U V W X Y Z

A Methanol
B Acetone
C Acetonitrile
D Dichloromethane
E Carbon Disulfide
F Toluene
G Diethylamine
H Tetrahydrofurane
I Ethyl acetate

EN ISO 374-1



X Y Z

J n-Heptane
K Sodium hydroxide 40%
L Sulphuric acid 96%
M Nitric acid 65%
N Acetic acid 99%
O Ammonia 25%
P Hydrogen peroxide 30%
S Hydrofluoric acid 40%
T Formaldehyde 37%

EN ISO 374-1



CUT

CUT RESISTANCE

A1 ≥ 200 G A4 ≥ 1500 G A7 ≥ 4000 G
A2 ≥ 500 G A5 ≥ 2200 G A8 ≥ 5000 G
A3 ≥ 1000 G A6 ≥ 3000 G A9 ≥ 6000 G

MICRO-ORGANISMS

EN ISO 374-5



Protection against bacteria, fungi

EN ISO 374-5



Protection against bacteria, fungi, virus

VIRUS

EN 511



COLD HAZARDS

PERFORMANCE LEVELS

0-4 0-4 0 or 1

Water permeability
Contact cold resistance
Convective cold resistance

EN 421



RADIOACTIVE CONTAMINATION

For more details: www.mapa-pro.com

MAPA[®]
PROFESSIONAL
www.mapa-pro.com

Solo 997

SPECIFIC ADVANTAGES

- Excellent dexterity thanks to flexibility and reduced material thickness
- Worn alone or as an outer-glove
- Recommended for oily environments in industry
- Previous name: Solo Blue 997

MAIN FIELDS OF USE

Automotive/mechanical industry

- Assembly of small oily parts

Aeronautics industry

- Work with composite materials (resins)

Laboratory

- Manufacturing of medicines
- Pharmaceutical preparation
- Research, analysis, handling of precision parts

INSTRUCTIONS FOR USE

Instructions for use

-It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the «CE»-type tests.

- It is not recommended to persons sensitized to dithiocarbamates to use these gloves.
- Put the gloves on dry, clean hands.
- These gloves are designed for single use only.
- Do not touch the external side of the gloves when taking them off. Fold back the cuff end and pull them off while turning them inside out.

Storage conditions

Store the gloves in their original packaging protected from direct sunlight, far from heat sources.

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- UE type certificate or CE type examination certificate

0075/014/162/02/19/0584-ext 02/02/19

- Issued by the notified body nr

0075

C.T.C. – 4 rue Hermann Frenkel - F- 69367 LYON Cedex 07

- Quality assurance certificat

0334 Asqual 14 rue des Reculettes -F-75013 PARIS