

VENICUT55



HEATNOCUT® KNITTED GLOVE Ref. VECUT55





HEATnocut® high performance polyethylene fibre. Gauge 10.

HEATnocut® fibre (high performance synthetic fibres).

COLOUR

Yellow-Grey

SIZE

07, 09, 10





Cutting / Perforation Wearing





Construction / Civil engineering





Light industry



Product's highlights & user's benefits HEATnocut® high performance polyethylene Very good level of abrasion resistance Very good level of abrasion resistance Food compatibility Cut level 5 Cut level C



Certifications and Standards



REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements

5: Dexterity (from 1 to 5)

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)

- 2: Resistance to abrasion (from 1 to 4)
- X: Resistance to cutting (from 1 to 5)
- 4: Resistance to tear (from 1 to 4)
- X: Resistance to puncture (1 to 4)
- C: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)

EN407:2004 Protective gloves against Heat & Fire risks (X = Unrealized test)

- X: Resistance to flammability (from 1 to 4)
- 1: Resistance to contact heat (from 1 to 4)
- X: Resistance to convective heat (from 1 to 4)
- X: Resistance to radiant heat (from 1 to 4)
- X: Resistance to small projections of liquid metal (from 1 to 4)
- X: Resistance to large projections of molten metal (from 1 to 4)



REGULATION (EU) 1935/2004 CONTACT WITH FOOD PRODUCTS

GLOB MIGR Food contact - Overall Migration

- .: Contact with wet or watery food
- .: Contact with fatty foods
- .: Contact with acidic foods

USA STANDARDS



ANSI-ISEA 105:2016 Hand protection

A3: Resistance to cutting by sharp objects (from A1 to A9)



References					
References	Bar code	COLOUR	SIZE	•	<u> </u>
VECUT5507	3295249157227	Yellow-Grey	07	120	12
VECUT5509	3295249157234	Yellow-Grey	09	120	12
VECUT5510	3295249157241	Yellow-Grey	10	120	12