

Miller 9099 Relief Step

SP302 Rev. A

Materials

Webbing:.....Polyester
 Buckles:.....Zinc plated steel
 Sleeve:.....PVC heat shrinkable tubing
 Thread:.....Polyester
 Button Snap:.....Steel
 Label:.....Tyvek®

Technical

Weight:.....0.15 lbs (0.68 kg)
 Max Working Load:.....400 lbs (181.44 kg)
 Max. Length:.....43" (1.09 m)



** The 9099 Relief Step is a one-time use device. Once it has been activated, it must be replaced with a new unit.*

The Miller 9099 Relief Step is designed to relieve suspension trauma after a fall arrest. OSHA states that suspension trauma can occur within minutes after a fall, while waiting for rescue. The average fall rescue time is 15 minutes. The Relief Step provides support and helps blood circulation until rescue. Small and lightweight, the Relief Step attaches to any brand/style full-body harness.

INSTALLATION INSTRUCTIONS



1. Mount to upper rear web strap by "choking" through loop (Be sure loop is past metal adjustments.)



2. Attach "pull tab" button loop to the front leg strap above buckle.

ACTIVATION STEPS



STEP 1: Unsnap and pull orange tab to deploy



STEP 2: Insert opposite foot into loop



STEP 3: Adjust length and step up to relieve pressure



Use two Relief Steps for optimum support

MILLER
by SPERIAN®