

# Miller MightEvac®

## Self-Retracting Lifelines with Emergency Retrieval Hoist

Miller MightEvac Self-Retracting Lifelines combine the superior performance and reliability of the best-selling MightyLite Self-Retracting Lifeline Series with a quick-activating retrieval mechanism for emergency evacuation.

- 20% lighter than competitive models provides significant long-term savings and lowers cost of ownership
- Promotes quick and easy rescue with a 4:1 mechanical advantage (average speed of 25-ft. [8 m] per minute)
- For emergency evacuation only
- Corrosion-resistant stainless steel & aluminum components
- Convenient, heavy-duty carrying handle
- 310-lbs. (140.6 kg) working capacity

Available in galvanized or stainless steel cable in lengths of 50-ft. (15 m), 100-ft. (30 m) and 130-ft. (40 m). Kevlar rope models available in lengths of 40-ft. (12 m) MR40KB-Z7/40FT, and 80-ft. (24 m) MR80KB-Z7/80FT.



MR100GB-Z7/100FT

SKU	Description	Weight
MR50GB-Z7/50FT	MightEvac w/50-ft. (15 m) of 3/16-in. (5 mm) galvanized cable w/mounting bracket & pulley	39 lbs. (18 kg)
MR100GB-Z7/100FT	MightEvac w/100-ft. (30 m) of 3/16-in. (5 mm) galvanized cable w/mounting bracket & pulley	59 lbs. (27 kg)
MR130GB-Z7/130FT	MightEvac w/130-ft. (40 m) of 3/16-in. (5 mm) galvanized cable w/mounting bracket & pulley	64 lbs. (29 kg)
MR50SB-Z7/50FT	MightEvac w/50-ft. (15 m) of 3/16-in. (5 mm) stainless steel cable w/mounting bracket & pulley	39 lbs. (18 kg)
MR100SB-Z7/100FT	MightEvac w/100-ft. (30 m) of 3/16-in. (5 mm) stainless steel cable w/mounting bracket & pulley	59 lbs. (27 kg)
MR130SB-Z7/130FT	MightEvac w/130-ft. (40 m) of 3/16-in. (5 mm) stainless steel cable w/mounting bracket & pulley	64 lbs. (29 kg)
MR40KB-Z7/40FT	MightEvac w/ 40-ft. (12 m) of Kevlar rope w/ mounting bracket & pulley	29-lbs. (13 kg)
MR80KB-Z7/80FT	MightEvac w/ 80-ft. (24 m) of Kevlar rope w/ mounting bracket & pulley	46-lbs. (21 kg)

Note: Locking Snap Hook - 3/4-in. (19 mm) gate opening. All connectors include 3,600-lb. gate-strength.

## Miller Complete Confined Space Entry and Rescue Systems

SKU	Description
MR50GC-Z7/50FT	MightEvac w/50-ft. (15 m) of 3/16-in. (5 mm) galvanized cable / 7-ft. (2 m) tripod / mounting bracket
MR100GC-Z7/100FT	MightEvac w/100-ft. (30 m) of 3/16-in. (5 mm) galvanized cable / 7-ft. (2 m) tripod / mounting bracket
MR130GC-Z7/130FT	MightEvac w/130-ft. (40 m) of 3/16-in. (5 mm) galvanized cable / 7-ft. (2 m) tripod / mounting bracket
MR50GX-Z7/50FT	MightEvac w/50-ft. (15 m) of 3/16-in. (5 mm) galvanized cable / 9-ft. (2.7 m) tripod / mounting bracket
MR100GX-Z7/100FT	MightEvac w/100-ft. (30 m) of 3/16-in. (5 mm) galvanized cable / 9-ft. (2.7 m) tripod / mounting bracket
MR130GX-Z7/130FT	MightEvac w/130-ft. (40 m) of 3/16-in. (5 mm) galvanized cable / 9-ft. (2.7 m) tripod / mounting bracket
MR50GCM-Z7/50FT	MightEvac w/50-ft. (15 m) of 3/16-in. (5 mm) galvanized cable / ManHandler Hoist w/65-ft. (20 m) of 3/16-in. (4.8 mm) galvanized cable / 7-ft. (2 m) tripod / mounting bracket
MR100GCM-Z7/100FT	MightEvac w/ 100-ft. (30 m) of 3/16-in. (5 mm) galvanized cable / ManHandler w/ 100-ft. (30 m) of 3/16-in. (5 mm) galvanized cable / 7-ft. (2 m) tripod/ mounting bracket
MR130GCM-Z7/130FT	MightEvac w/ 130-ft. (40 m) of 3/16-in. (5 mm) galvanized cable / ManHandler w/ 100-ft. (30 m) of 3/16-in. (5 mm) galvanized cable / 7-ft. (2 m) tripod/ mounting bracket
MR50GXM-Z7/50FT	MightEvac w/50-ft. (15 m) of 3/16-in. (5 mm) galvanized cable / ManHandler Hoist w/65-ft. (20 m) of 3/16-in. (4.8 mm) galvanized cable / 9-ft. (2.7 m) tripod / mounting bracket
MR100GXM-Z7/100FT	MightEvac w/ 100-ft. (30 m) of 3/16-in. (5 mm) galvanized cable / ManHandler w/ 100-ft. (30 m) of 3/16-in. (5 mm) galvanized cable / 9-ft. (2.7 m) tripod/ mounting bracket



Note: Confined Space Systems also include a pulley, carabiner and two heavy-duty equipment bags. For stainless steel wire rope, change the "G" to an "S" in the corresponding SKU number (Ex: MR50GC/50FT becomes MR50SC/50FT and MR130GC/130FT becomes MR130SC/130FT). Note: ManHandler Hoist only available in 65-ft. (20 m) and 100-ft. (30 m) lengths. Locking Snap Hook - 3/4-in. (19 mm) gate opening. All connectors include 3,600-lb. gate-strength.

## Miller ManHandler® Hoist/Winch

The Miller ManHandler Hoist/Winch is the perfect solution for a range of applications including confined space entry, rescue, positioning and personnel/material handling.

*A secondary fall arrest system is recommended for fall protection.*

- Compact, durable steel construction
- Smooth, controlled winding action
- Effortless lifting and lowering with 5:1 gear ratio
- Anti-backlash crank handle braking system prevents freewheeling
- Built-in mounting bracket
- 350-lbs. (159 kg) working capacity

SKU	Description
8442-Z7/65FT	ManHandler Hoist w/65-ft. (20 m) of 3/16-in. (5 mm) galvanized cable
8442GC-Z7/65FT	ManHandler Hoist w/65-ft. (20 m) of 3/16-in. (5 mm) galvanized cable & 7-ft. (2 m) tripod
8442-Z7/100FT	ManHandler Hoist w/100-ft. (30 m) of 3/16-in. (5 mm) galvanized cable
8442GC-Z7/100FT	ManHandler Hoist w/100-ft. (30 m) of 3/16-in. (5 mm) galvanized cable & 7-ft. (2 m) tripod
8440-Z7/60FTBR*	Material Winch w/60-ft. (18 m) of 3/16-in. (5 mm) galvanized cable
8441-Z7/88FT*	Material Winch w/88-ft. (27 m) of 3/16-in. (5 mm) galvanized cable

\* Also available with stainless steel cable by adding "SS" after the model number (Ex: 8442SS-Z7/65FT).

Note: Locking Snap Hook - 3/4-in. (19 mm) gate opening. All connectors include 3,600-lb. gate-strength.



8442-Z7/65FT

## Miller Tripod

The versatile, lightweight Miller Tripod is designed for typical confined space and rescue applications.

- Available in 7-ft. (2 m) and 9-ft. (2.7 m) models
- High-strength aluminum construction
- Withstands up to 5,000-lbs. (22 kN) of vertical pull
- Adjustable legs with integral push pins, ideal for uneven surfaces
- Independent leg locking feature holds legs securely in place
- Safety chain and tripod feet with rubber skid pads and serrated edge prevent slippage in icy conditions
- Includes reflective tape

SKU	Description
51/7FT	7-ft. (2 m) high-strength aluminum Tripod
51X/9FT	9-ft. (2.7 m) high-strength aluminum Tripod

