



KPR®



BRINGING TECHNOLOGY INTO SAFETY



• PROTECTION

Extra wide toe cap for comfort. Quality checked and tested to meet CE EN ISO 20345 standards. Protective scuff toe was designed to help protect and prolong the life of the safety shoe. Steel midsole for work environments that require protection from sole penetration.

• UPPER

Buffalo full grain printed leather
Full Inner Lining
Light Weight



• OUTSOLE

Dual Density Injected Polyurethane to provide both work functionality, comfort, light weight, and non-marking. New innovation to provide ultimate slip resistance performance. Tread designed for superior traction, stability, heel shock absorption, and easy clean.



• EXTRA WIDE TOE CAP GREAT FITTING



• FOOTBED

Removable Thick Cushion PU footbed. Comfort heel cushion, arch stability, and air channel system.



SPECIFICATIONS

Model	L-026X
Safety Toe	Steel toe cap
Sole protection	Steel plate
Electrical feature	ESD
Material	Buffalo full grain printed leather
Color	Black
Lining	BK mesh lining
Sole	Dual density PU/PU outsole, SRC
Size	UK 2-13 / EU 35-48
Footbed	Thick cushion EVA, Provide support, comfort and stay dry

• KPR SLIP RESISTANCE TEST RESULTS

	Coefficient of Friction		
		Requirement	KPR L-sole Results*
SRC (SRA +SRB)	SRA Ceramic Tile + SLS	Forward Flat Slip 0.32	0.62-0.63
		Forward Heel Slip 0.28	0.49-0.50
	SRB Stainless Steel + Glycerol	Forward Flat Slip 0.18	0.64-0.69
		Forward Heel Slip 0.13	0.22-0.23

*Slip resistance testing conducted by Intertek (2011)

www.kprsafety.com



L-026X-U0025