

# **ULTRANE 526**

Grip assured, skin protected and unbeatable fingertip sensitivity in very oily environments.

## **SPECIFIC ADVANTAGES**



### Comfort

• Unbeatable fingertip sensitivity



### Durability

Excellent abrasion resistance due to the nitrile coating



### **Productivity**

• Grip and Proof coating ensures an excellent grip in very oily environment. It also reduces muscle strain and boosts productivity



### Skin protection

- Oilproof, it repels oil penetration and reduce dermatitis
- Free of harmful substances: DMF Free



### **Guaranteed quality**

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting



#### Washability

• Washable 3 times at 40° without any alteration on performances\* to extend lifespan, reduce costs and waste





4121A

CAT.3



EN407

**GRIP & PROOF** 

**TECHNOLOGY** 



X1XXXX

ISO 13997:

5 N



ISO 18889

DEXTERITY EN 420:

5/5

# INDUSTRIES

- Automotive/mechanical industry
- Mechanical industry
- Local Authorities (Parks and Public Spaces)
- Glass industry
- Agriculture sector

### **APPLICATIONS**

- Re-entry tasks
- Handling and sorting small, sharp parts
- Handling oily mechanical parts
- Machining parts using cutting oil
- Mechanical maintenance
- Handling glass sheets
- Public park maintenance
- Assembly of small oily parts
- Maintenance in wet environments (water, oil, greases, hydrocarbons)



Tests carried out on unworn gloves (i.e. in new condition) which differs from the reality in the field.





## **ULTRANE 526**

## LEGENDS

EN388

**MECHANICAL HAZARDS** 



PERFORMANCE LEVELS (X = NOT TESTED)

4 1 2 1 A

0-4 0-5 0-4 0-4 A-F P

| Impact protection (optional)

| Cut resistance according to ISO | 13997

| Puncture resistance | Tear resistance

EN407

Abrasion resistance

THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)



Blade cut resistance

Resistance to large quantities of molten metal

Small splashes of molten metal

Radiant heat resistant
Convective heat resistance
Contact heat resistance
Limited flame spread



PROTECTION FROM PESTICIDES

GR: Re-entry tasks

ISO 18889

## PRODUCT DETAILS

Interior finish	Seamless textile support
Gauge	13
Exterior finish	Fully-coated
Material	Nitrile GRIP&PROOF coating
Cuff characteristic	Knitted Cuff
Colour.s	Black
Length (cm)	2-3
Size	7 8 9 10 11

## LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag
	96 pairs/carton

## **LEGISLATION**

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation  $n^{\circ}$  1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/09/18/1953 ext 01/09/18
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0075 | CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE

