



**BLUE EAGLE®**

**CE EN812**



## Face Shield Visor

**PRODUCT NAME: FC48G5**

**STANDARD: EN166, ANSI Z87.1, Z94.3 // CE2-5, ANSI U6**

**CLOUR BLUE: DARK GREEN (SHADE 5)**

**SIZE: 20 CM X 39 CM THICKNESS 1.0 MM**

### Description

- **Best optical quality**  
To provide users with the best vision possible and help them better focus on their task, Blue Eagle faceshields have passed the highest levels of optical tests (Class 1), including spherical refractive power, astigmatic refractive power, prismatic refractive power, and light diffusion.
- **Aluminum reinforcements**  
Aluminum edge reinforcements can help improve visor strength. A user can also easily bend or adjust the visor to suit usage requirements.
- **High-speed particle impact resistance at extremes of temperatures, 120 m/s**  
The faceshield is made using extrusion-grade polycarbonate (PC) with the highest specifications for mechanical strength, allowing it to withstand the impact of a 6 mm steel bead traveling at a speed of 120 m/s at extremes of temperatures.
- **Superb UV protection**  
We used advanced technologies to provide the user with superb protection against UV.
- **Resistance to ignition**  
European Standard testing was used. An iron rod measuring 6 mm in diameter and 300 mm in length was heated at one end to a temperature of 650°C. The heated end was pressed against the sample surface using its own weight for 5 seconds. The faceshield did not catch fire nor glow red.
- **Quick and easy visor replacement**

**Made in Taiwan**

**WWW.BLUEEAGLE-SAFETY.COM**

**282 HEPING SECOND ROAD, KAOHSIUNG 80651, TAIWAN**